



**Technical Data Sheet:**  
**Synthetic Thinner Extra 608**

**Code:**  
**1608**

**Sigla:** ST608  
**Rev.:** 8  
**Date:** 17/01/18

**Product Type:**

Specific thinner for dilution of synthetic paints.

**Formats:**

Tank: 1000 liters,  
Drum: 200 liters,  
Cans: 25 - 20 - 10 - 5 - 1 liters.

**Product Characteristics:**

Product consist of naphtha solvents with high solvent power.  
It has a slightly stronger odor than normal white spirit and a faster evaporation, but the balanced formula determines a perfect dilution of the paints.

**Technical Specifications of the Product:**

CHARACTERISTICS	UM	VALUE	METHOD	TOLERANCE
Physical Aspect		Liquid	Visual	//
Color		Colorless clear	Visual	//
Flash point	°C	10	Met. Int. ISTR. 53	Typical
Water content	%	0.3	Met. Int. ISTR. 48	Max
Density at 20°C	Kg/dm <sup>3</sup>	0,865	Met. Int. ISTR. 44	± 0,005

**Use / Applications:**

Specific product for the dilution of synthetic paints, oleo-synthetic, anti-rust primers, fast drying synthetic varnishes and nitro synthetic paints.

It gives flow and shine to the paint, offering also the possibility of applying a second coat without the risk of removing the first one.

**Furthermore:**

It can also be used for degreasing and cleaning the surfaces before painting and for all the equipment.  
For degreasing, washing and cleaning jobs in the bodywork; refer to products in accordance with Legislative Decree 27 March 2006 n.161.

**How to use:**

Dilute the paint to obtain the optimal viscosity for the chosen application. Thicker for brush or roller and more liquid for spray application. Approximately between 10 and 20%, unless otherwise indicated on the paint can.

**Further information: //**

*The above information is given according to our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the Fidea SpA control.*