



Technical sheet:
Polyurethane thinner 620

Code:
1396

Sigla: ST396
Rev.: 7
Data: 07/12/17

Type of product:
Polyurethane thinner

Packages:
1000Lt tanks
200Lt drums
25-10-5-1Lt cans

Product features:

Mixture of pure solvents with a characteristic fruit flavor.

Technical specifications of the product:

CHARACTERISTIC	UM	VALUE	METHOD	TOLLERANCE
Physical state		Liquid	Visual	//
Color		Colourless limpid	Visual	//
Density at 20°C	Kg/dm ³	0,863	Met. Int. ISTR. 44	± 0,010
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

Use/Application:

Specific product used for diluting catalyzed and monocomponent polyurethane varnishes.

Usage instructions:

Dilute the varnish till obtaining the desired viscosity. More dense for rolling brushes and more liquid for spraying guns.

We recommend to use a retarder (*see other info*) during the summer season due to high temperatures or high humidity levels throughout the day.

Other info:

Reccomended product "Retarder 509".

The information indicated above are all part of our knowledge and applications. FIDEA spa is not responsible for the final usage of the product as it is not under our control.