



Technical Data Sheet:
Nitro anti-fog thinner 412

Code:
1118

Ref.: ST118
Rev.: 13
Date:
21/10/2019

Product Type:

Thinner for nitrocellulose paints.
Chlorinated Free

Formats:

Tanks 1000 liters,
Drums 200 liters,
Cans 25- 10 - 5 - 1 liters.

Product Characteristics:

Product formulated with pure raw materials giving it a very faint and tolerable odor.
It contains a high percentage of acetates and glycols.

Technical Specifications of the Product:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Density at 20°C	Kg/dm ³	0.840	Met. Int. ISTR. 44	± 0.005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

Use / Applications:

It gives nitro paint good cutting power, perfect flow, shine and, above all, excellent ANTI-BLEACHING power, which allows for its use in all temperature and humidity conditions, even the most unfavorable.

And also:

Since it is an extremely versatile product, it is also suitable for anti-fouling paints, epoxy paints, nitro paints for wood, nitro insulation for construction, metal zinc, etc.

How to use:

Dilute the enamel to the desired viscosity for the chosen application.

Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

Additional Information:

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Product limit value ready to use (g/l) – D.Lgs. n. 161/06
Preparatory and cleaning product	Preparation product	850

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA