



**Technical Data Sheet:**  
**Nitro anti-fog thinner 709**

**Code:**  
**1816**

**Ref.:** ST816  
**Rev.:** 9  
**Date:** 20/07/2021

**Product Type:**

Thinner for nitrocellulose paints.

**Formats:**

Tanks 1000 liters,  
Drums 200 liters,  
Cans 25 - 20 liters.

**Product Characteristics:**

Product partly formulated with pure raw materials and partly with source pure raw materials.

**Technical Specifications of the Product:**

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color	Hazen	< 15	Comparison to STD	//
Flash point	°C	< 0 (closed cup)	Met. Int. ISTR. 53	//
Density at 20°C	Kg/dm <sup>3</sup>	0.870	Met. Int. ISTR. 44	± 0.02

**Use / Applications:**

Nitro thinner suitable to dilute nitro primers and rust inhibitors  
It is also suitable for all general uses.

**How to use:**

Dilute the paint to the desired viscosity for the chosen application (brush or roller). Approximately between 10 and 20 %, unless there are different indications printed on the paint can.  
For good anti-bleaching power, add 5 to 7% of Retardant for Nitro Thinner 431

**Additional Information: //**

*The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA*