



**Technical Data Sheet:**  
**Nitro anti-fog thinner 750**

**Code:**  
**1391**

**Ref.:** ST391  
**Rev.:** 12  
**Date:**  
21/10/2019

**Product Type:**

Thinner for nitrocellulose paints.

**Formats:**

Tanks 1000 liters,  
Drums 200 liters,  
Cans 25- 20- 10 - 5 - 1 liters.

**Product Characteristics:**

Product formulated with pure raw materials, with a very tolerable and faint odor and with a slight anti-bleaching power.

**Technical Specifications of the Product:**

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Density at 20°C	Kg/dm <sup>3</sup>	0.845	Met. Int. ISTR. 44	± 0.005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

**Use / Applications:**

Versatile thinner suitable for diluting nitrocellulose paints, primers, rust inhibitors, fast-drying synthetic enamels.

**How to use:**

Dilute the enamel to the desired viscosity for the chosen application.  
Approximately between 10 and 20 %, unless there are different indications printed on the paint can.  
The anti-bleaching power of this product can be increased by adding 6-8% of retardant (our product 'Retardant for Nitro Thinners 431').

**Additional Information:**

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Limit value of ready-to-use product (g/l) - Legislative Decree No. 161/06
Preparation and cleaning products	Preparation product	850

*The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA*