



Technical Data Sheet:
Polyurethane Thinner 614

Code:
1150

Ref.: ST150
Rev.: 7
Date: 30/03/2020

Product Type:
Thinner for polyurethane paints.

Formats:
Tanks 1000 liters,
Drums 200 liters,
Cans 25 -10 - 5 - 1 liters.

Product Characteristics:
Blend of pure solvents.

Technical Specifications of the Product:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visivo	//
Color		Colorless clear	Visivo	//
Density at 20°C	Kg/dm ³	0.877	Met. Int. ISTR. 44	+ 0,005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	<0	Met. Int. ISTR. 53	Typical

Use / Applications:

It is an excellent product for all paint finishes, even under average unfavorable temperature and humidity conditions, by giving the paint flow and shine, without spots or pinholes.

How to use:

Dilute the paint to the desired viscosity for the chosen application: thicker for brush or roller, more liquid for spray application.

Only when operating in very adverse weather conditions or for lacquered paints, we recommend adding to thinner some 20 to 30% of our Retardant 509.

Additional Information: //

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA