



Technical Data Sheet:

**Thinner for Polyurethane
Paints 617**

Code:
1269

Ref.: ST269
Rev.: 4
Date:
15/09/2021

Product Type:

Thinner for polyurethane paints.

Formats:

Tanks 1000 liters
Drums 200 liters
Cans 25 - 5 - 1 liters

Product Characteristics:

Blend of pure solvents with a distinctive aromatic odor.
It contains low and medium boiling ketones that give it high solvent power.

Technical Specifications of the Product:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Density at 20°C	Kg/dm ³	0.860	Met. Int. ISTR. 44	± 0.01
Flash point	°C	32	Met. Int. ISTR. 53	Typical

Use / Applications:

This product is used for diluting polyurethane paints in the bodywork industry and the iron sector. It combines high solvent power with slow evaporation, which allows for a perfect flow and shine to the paint.

How to use:

Dilute the paint to the desired viscosity for the chosen application. It is suitable for both air drying and oven drying

Additional Information: //

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA