



Technical Data Sheet:
Polyurethane Thinner 648

Code:
1152

Ref.: ST152
Rev.: 5
Date: 02/12/2010

Product Type:
Thinner for catalyzed polyurethane paints.

Formats:
Tanks 1000 liters,
Drums 200 liters,
Cans 25 liters.

Product Characteristics:
Blend of pure solvents with characteristic fruity odor.

Technical Specifications of the Product:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	VISIVO	//
Color		Colorless clear	VISIVO	//
Density at 20°C	Kg/dm ³	0.855	Met. Int. ISTR. 44	+ 0,005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	<0	Met. Int. ISTR. 53	Typical
Index of refraction at 20°C	IR	1.438	Met. Int. ISTR. 46	+ 0,005

Use / Applications:

This product has been specially designed for diluting catalyzed polyurethane paints. Its specially balanced formulation makes it ideal for automatic paint systems where there are requirements for fast drying as well as excellent finish, gloss, and absence of pockmarks or pinholes.

How to use: //

Additional Information: //

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA