



Technical Sheet:
POLYURETHANE THINNER 650

Codice:
1372

Sigla: ST372
Rev.: 6
Data: 02/02/18

Product Information:

Thinner for polyurethane paints.

Formats:

Tanks 1000 liters,
Drums 200 liters,
Can 25 liters.

Product Characteristics:

Blend of pure solvents with a characteristic fruity smell.

Technical Specifications of the Product:

CHARACTERISTICS	UM	VALUE	METHOD	TOLERANCE
Physical Aspect		Liquid	Visual	//
Color		Clear Colorless	Visual	//
Density at 20°C	Kg/dm ³	0,885	Met. Int. ISTR. 44	± 0,005
Water content	%	0.3	Met. Int. ISTR. 48	Max
Flash Point	°C	< 0	Met. Int. ISTR. 53	Typical

Use / Applications:

It is great for a high-quality finish paint also to dilute lacquer paint. It gives the paint flow and brilliance without leaving pinholes or cracks.

It can be used at any time of year, even in unfavorable temperature and humidity conditions.

How to use:

Dilute the paint to obtain the optimal viscosity for the chosen application: thicker for a brush or roll and more liquid for spray use.

Further information:

Only for lacquered paints; if you operate in particularly adverse weather conditions, 10-20% of "Retardant" should be added to the diluent. Article 509 ".

The above information is given according to our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the Fidea SpA control.