



Technical Data Sheet:
SOUND ABSORBER
Soundproofing

Code:
2718

Ref.: ST718
Rev.: 4
Date:
21/03/2016

Product Type: Soundproofing and water-repellent protective coating for sheet metal.	Formats: Cans 2.5 - 0.5 liters
Nature of binding agent: Oxidized bitumen.	Nature of pigment: Inert charges with high hiding power.
Technical Specifications of the Product: Viscosity: thixotropic Color of paint in can: color of bitumen Density (Kg/l): 1.560± 0.02 Yield (m ² /lt): 1.5- 2 Dry Residue: 82 % ± 2 %	
Use / Applications: Soundproofing and water-repellent protective coating for sheet metal. It can be used in particular for wheel arches and underbody of cars, as it resists crushed stone and the aggressive action of mud. It can also be used whenever sheet metal protection is needed in general.	
How to use: The product can be applied by using a palette knife, a brush or spray with suitable soundproofing guns. The recommended thickness for application is 1 to 2 mm.	Drying: Dust off: 10-15 minutes; Touch: 45 minutes; In depth: 12- 18 liters.
Additional Information: Store in a cool, dry place and in a well-sealed can. Recommended to be used within 12 months of purchase.	
<i>The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA</i>	