



Technical Data Sheet:
Antisil 30- Anti-Silicone Solvent

Code:
1158

Ref.: ST158
Rev.: 5
Date: 05/08/2020

Product Type:

Solvent for the solubilisation of silicone oils.

Formats:

Cans 25 - 5 - 1 liters,
Drums 200 liters.

Product Characteristics:

Blend of pure solvents.

It has a medium evaporation rate that allows deep cleaning without leaving greasy films.

It has good solvent power, which is much higher than other products containing mineral white spirit.

Technical Specifications of the Product:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Density at 20°C	Kg/dm ³	0.780	Met. Int. ISTR. 44	± 0.005
Water content	%	0.04	Met. Int. ISTR. 48	Maximum
Flash point	°C	15	Met. Int. ISTR. 53	Typical

Use / Applications:

This product is especially suitable for removing protective waxes and silicones from car bodies.

It perfectly prepares the surface for paint application without affecting or matting primer paints.

Furthermore:

It can also be used to remove grease, tar and general dirt from any surface: metal, glass, plastic, painted furniture, etc.

How to use:

It can be used with a rag, paintbrush or spray, then wiped over with a clean cloth.

Medium evaporation allows it to be used in all seasons and for large areas.

Additional Information:

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Limit value of ready-to-use product (g/l) - Legislative Decree No. 161/06
Preparation and cleaning products	Preparation product	850

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA