

Scheda tecnica:

Terminator - Antitarlo

Codice: 1A47

Sigla: ST650 Rev.: 9 Data: 14/03/16

Product type:

ODORLESS ANTI-WOODWORM FUNGICIDE AND PROTECTION for wood

Surgical medical presidium

Authorization Ministry of Health no. 18805

Packages:

Drums/Cans 25 - 5 - 1 - 0,250 litres.

Product Features:

Composition per 100g: Permethrin 0.325 g / L, Isoparaffinic Solvents q. b.

Terminator exceeds on the test of effectiveness against larvae of the Hylotrupes bajulus according to the European Protocol UNI EN 46, as well as against xylophagous fungi basidiomycetes type Coniophora puteana, Coriolus versicolor, Poria placenta, Gloeophyllum trabeum, according to UNI EN 113 criteria.

Technical Specification:

CHARACTERISTICS	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Clear colorless		Visual	//
Density at 20°C	Kg/dm ³	0,770	Met. Int. ISTR. 44	± 0,005
Flash point	°C	62	Met. Int. ISTR. 53	Tipico
Refractiv index at 20°C	IR	1,425	Met. Int. ISTR. 46	± 0,005

Drying 1	time:
----------	-------

The wood can be painted over after 18-36 hours (depending on the season)

Anti-Woodworm Action (makes

wood not eatable for the insects): The active ingredient has durability and effectiveness for 10 years

Stability:

The active substance remains stable for at least 2 years of storage, also at 50 ° C. It does not degrade to light.

Terminator Anti-woodworm Coverage:

Protective and Preventive Action: 8 - 10 m²/Litre.

Healing and disinfectant action: 4 - 5 m²/Liter (depending on the type and deterioration of the surface to be treated). Then apply a cellophane sheet (gas chamber action) for 2/3 days.

Uses / applications:

Terminator It is ruthless with woodworm, but at the same time gentle with operators:

It is colorless, odorless and non-flammable.

Specially designed for the disinfestation and protection of antique furniture, wood sculptures, frames, beams, wooden floors, etc.., from termites, insects, mold and mildew.

It preserves every kind of wood from xylophagous insects (Worm, Sirex, Capricorn, lyctus) and their larvae.



Scheda tecnica:

Terminator - Antitarlo

Codice: 1A47

Sigla: ST650 Rev.: 9 Data: 14/03/16

Use Instructions:

Protective and Preventive Action: Terminator is applied by brush or immersion.

Healing and disinfectant action (Wood already attacked by termites): it is recommended to thoroughly wet the artifact with a brush or spray and then repaint (See Drying time).

For a targeted action: in the case of small wood attack, it is recommended to put the product directly into the holes, with a common syringe.

Further information:

It is not corrosive to metals or light alloys, It does not damage glues or paints, wax polishing, shellac, does not remove gilding or tempera paints, does not alter coatings with antique textiles or paper.

It leaves no residue or greasiness and can be painted over (See Drying time).

Can be added to straw-oil.

The information indicated above are all part of our knowledge and applications. Fidea spa is not responsible for the final usage of the product as it is not under our control.