



**Technical Data Sheet:**  
**Thinner for Epoxy Paints 123**

**Code:**  
**1127**

**Ref.:** ST127  
**Rev.:** 10  
**Date:** 20/09/2021

**Product Type:**  
Thinner for epoxy paints.

**Formats:**  
Tanks 1000 liters,  
Drums 200 liters,  
Cans 25 - 5 - 1 liters

**Product Characteristics:**

Product formulated with pure raw materials with high percentages of low and medium boiling ketones.

**Technical Specifications of the Product:**

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Density at 20°C	Kg/dm <sup>3</sup>	0.860	Met. Int. ISTR. 44	± 0.010
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

**Use / Applications:**

It has very high solvent power, which is indispensable for diluting epoxy paints, polyamide epoxy paints and amine epoxy paints, either air drying or oven drying (at medium temperature). The product is essential for perfect flow and catalysis of the paint, bringing out its shining characteristics.

**Furthermore:**

The Thinner for Epoxy Paints 123 is also excellent for cleaning equipment stained with fresh or medium-dry paint.

For degreasing, washing and cleaning operations in the bodywork sector, please refer to products that comply with Legislative Decree No. 161 of March 27, 2006.

**How to use:**

Dilute the paint following the paint manufacturer's recommendations or in any case until the right viscosity is obtained for the chosen application.

Mix carefully.

**Additional Information: //**

*The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA*