



**Technical Data Sheet:**  
**Tire Rebuilding Solvent 3906**

**Code:**  
**1278**

**Ref.:** ST278  
**Rev.:** 3  
**Date:** 01/12/2010

**Product Type:**  
Tire Rebuilding Solvent.

**Formats:**  
Tanks 1000 liters  
Drums 200 liters,  
Cans 25 liters.

**Product Characteristics:**  
Solvent containing aliphatic hydrocarbons characterized by a very faint and tolerable odor.

**Technical Specifications of the Product:**

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Flash point	°C	< 0 (closed cup)	Met. Int. ISTR. 53	//
Water content	%	0.1	Met. Int. ISTR. 48	Maximum
Density at 20°C	Kg/dm <sup>3</sup>	0.720	Met. Int. ISTR. 44	± 0.005
Index of refraction at 20°C	IR	1.400	Met. Int. ISTR. 46	± 0.005

**Use / Applications:**

This product is specifically designed for the tire rebuilding industry and is used for the production of the binding solution and black paint.

It ensures that the rebuilt tire does not come off.

It is also an excellent solvent for cleaning the tire before processing.

**How to use:**

Having a very faint and tolerable odor, it is highly appreciated by users.

Use away from flames and sparks.

**Additional Information: //**

*The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA*