



Technical Data Sheet:
Putty paste

Code:
2400

Ref.:ST2400
Rev.: 3
Date: 27/06/2022

Product Type:

Putty paste

Formats:

25 - 5 - 1 - 0.500 - 0.250 kg

Product Characteristics:

French-type putty paste

Technical Specifications of the Product:

CHARACTERISTIC	UM	VALUE
Physical state		Doughy
Color		White
Granulometry	micron	9- 11
Specific weight		L 1 = Kg. 1.750± 0.005
Start of product setting time		Already mixed
End of product setting time		6-8 hours (see the following section "Drying")

Drying:

6-8 hours to the touch under normal humidity conditions.
It can be painted after 24 hours.

Dilution:

Dilute only the amount needed.

Available colors:

WHITE

Use / Applications:

Ready-to-use product with the right consistency for smoothing, grouting and repair work on wood or walls, for interior use only.
It has a predetermined density that makes it workable with a trowel, so it should be applied just as it is.
It is fast drying, non-shrinking and non-yellowing.
It has considerable filling power, adhesive strength and good workability even with dry sanding.

How to use:

Application with trowel.

Additional Information:

It can be overpainted (see Drying) with both water-based and synthetically solvent-based products, without stripping or excessive absorption.
Store away from heat sources. Protect from frost.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA