



Technical sheet:
Paint Remover 1052 NEW

Code:
1761

Sigla: ST761
Rev.: 1
Data: 04/05/18

Type of product:
Paint remover for varnishes and paints

Packages:
Drums 200 lt, cans of 20 - 4 - 0,750 - 0,375 lt

Product characteristics:

Product based on organic solvents free of Dichloromethane, according to the provisions of Regulation (EU) no. 276/2010, which modifies the REACH regulation.

Technical specifications of the product:

CHARACTERISTICS	UM	SPECIFIC VALUE	METHOD	TOLLERANCE
Physical state		Pasty	Visual	//
Color		Green	Visual	//
Density at 20°C	Kg/dm ³	0.930	Met. Int. ISTR. 44	± 0,02

Performance: 2 m²/l aprox

(this value is approximate as it highly depends on who applies it, on how thick the paint layer is, on the characteristic of the surface and from the temperature of the environment)

Action times:

10-20 minutes for synthetic paints and water-based varnishes

30-60 minutes for polyurethane paints

Usage/applications:

The particular formulation and efficacy of this product offers a great VERSATILITY.

It is effective on synthetic paints, also with several layers, oil paints, nitrocellulose, acrylic, polyurethane, cold enamels, water-based paints and plastic wall, putty, adhesives for carpet and parquet.

It is particularly suitable also in the nautical and stone sector.

Its density allows a perfect and homogeneous application both on horizontal and vertical surfaces.

Instructions:

Stir the product after opening the can.

Apply a thick layer of paint remover with a brush or spatula, wait for the product to penetrate the surface, then remove the entire layer with a spatula or cloth.

In case of use on wood, being the natural and variable support, it is advisable to carry out an application test in a small area that is not very visible, to avoid possible undesired effects.

Additional instructions:

Avoid applying the product on plastic surfaces and on both hot and sun exposed temperatures.

Do not shake before use. Open the cap with caution because the product may discharge violently if under pressure; then cover the mouthpiece with a rag and pull the opening ring slowly, until it is vented, keeping the container away from the face.

Use protective gloves and glasses during application.

Store the product tightly closed, away from heat and in a cool dry place.

The wastes generated by the use of this product must be considered hazardous and disposed by specialized companies.

We are not responsible for any un-appropriate use of the products.

Product not suitable for the bodywork.

The information indicated above are all part of our knowledge and applications. FIDEA spa is not responsible for the final use of the product as it is not under its control.