



Technical Data Sheet:
Liquid Paint Remover SC

Code:
1157

Ref.: ST157
Rev.: 0
Date:
14/06/2011

Product Type:

LIQUID paint remover for cleaning equipment.

Formats:

Plastic jerry cans of 20 liters.

Product Characteristics:

It is LIQUID like a normal thinner since it does not contain any thickeners.

Technical Specifications of the Product:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless	Visual	//
Density at 20°C	Kg/dm ³	1.070	Met. Int. ISTR. 44	± 0.01

Action times:

Action times depend on the type of paint, thickness and coats applied.

Approximately: 10-20 minutes for synthetic paints and water-based varnishes, 1-2 hours for polyurethane paints, and 10-24 hours for polyester paints and oven-baked enamels.

Use / Applications:

It is used for removing paint from artifacts protected by synthetic, oleosynthetic paints, including multilayer (e.g. shutters), nitrocellulosic, acrylic, polyurethane, etc.

It is also used for accurate cleaning of equipment used for painting, when the paint is partially dried and therefore where normal nitro thinner would not be sufficient.

For washing and cleaning operations in the bodywork sector, please refer to products that comply with Italian Legislative Decree No. 161 of March 27, 2006.

How to use:

Since it is perfectly liquid, it should be used by immersion in the tank.

Wipe off the removed paint with a palette knife or straws, then wash and degrease the artifact with nitro thinner or water, let dry and then repaint.

Additional Information:

Avoid use on plastics and fiberglass.

For use in tanks, be careful to use tanks made of stainless steel, galvanized sheet metal or PEHD.

Since the product evaporates quickly, it is necessary to hermetically seal the tank when not in use.

Warnings:

Do not shake before use. Open the cap carefully as the product may leak out violently when under pressure; then cover the opening with a cloth and pull the opening ring slowly until venting occurs, always keeping the container away from the face.

Use goggles and protective gloves during application, store the container tightly closed, away from heat sources and in a cool, dry environment.

Do not apply to hot or sun-exposed surfaces.

Waste produced by the use of the paint remover should always be considered hazardous and disposed of by qualified companies.

We decline any responsibility for damage resulting from any other handling of the container.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA