



Technical Data Sheet:
Svernilegno SC

Code:
1536

Ref.: ST536
Rev.: 9
Date:
04/05/2018

Product Type:

Specific paint remover for wood.

Formats:

Cans 4 and 0.750 liters

Product Characteristics:

Dichloromethane-free organic solvent product in accordance with Regulation (EU) No. 276/2010, amending the REACH regulation.

Technical Specifications of the Product:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Doughy	Visual	//
Color		Light blue	Visual	//
Density at 20°C	Kg/dm ³	0.930	Met. Int. ISTR. 44	± 0.02

Yield:

about 2 m²/l

(this value is approximate as it depends greatly on the tool used for application, the type and thickness of the paint, the characteristics of the surfaces, and the ambient temperature).

Action times:

10-20 minutes for synthetic paints and water-based varnishes;
30-60 minutes for polyurethane paints;
4-10 hours for polyester paints.

Use / Applications:

Specific product for wood applications.

It removes any type of paint: two-component polyurethane paints, polyester paints, nitrocellulose paints, acrylic paints, epoxy paints, synthetic paints and oil-synthetic paints, plasters, etc., without bleaching, staining or damaging the wood.

It is particularly suitable for restoration work, in crafts and DIY work.

It is also recommended in the marine industry.

It has an optimal density that allows it to penetrate even the most difficult-to-reach areas and to be applied even vertically.

How to use:

Stir the product after opening the container.

Apply the paint remover on the artifact with a thickness of 2 to 3 mm, let it work (see Action times) and remove all traces of product and paint with a rag or palette knife.

Since wood is a natural and variable substrate, it is advisable to test the application in a small, barely visible area to avoid possible undesirable effects.

Warnings:

Avoid use on plastics.

Do not shake before use. Open the cap carefully as the product may leak out violently when under pressure; then cover the opening with a cloth and pull the opening ring slowly until venting occurs, always keeping the container away from the face.

Use goggles and protective gloves during application.

Store the container tightly closed, away from any heat sources and in a cool, dry environment.

Waste produced by the use of the paint remover should always be considered hazardous and disposed of by qualified companies.

We decline any responsibility for damage resulting from any other handling of the container.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of Fidea SpA